CLA712

3.5 mm Jack male stereo - 2 x XLR male

Highlights:

- 28 AWG thin and dense stranded conductors
- Flexible PVC jacket
- Spiral shielding
- 4.0 mm (Ø) outer diameter
- Oxygen free copper



Product information:

The CLA712 is fitted with two 3-pin XLR males and a 3.5mm jack male stereo connector, constructed using the SIG144 cable. The easy to handle PVC jacket is excellent for fixed indoor and mobile applications. The inner conductors are fitted with a durable shielding. This gives an excellent protection against interference of all kinds such as electromagnetic fields produced by dimmers, electric motors or power cables. The SIG series cables are “all-round” signal cables which are suited for all kinds of applications where reliable signal transmission is needed. It comes in lengths of 1.5 meters to 3 meters, providing solutions for all applications.

Components:

- CableType: SIG144 - Signal Cable


Properties:



Product Features:

Application	AV & IT
Series	Classic Series

Wiring Diagrams:



Variants:

- CLA712/1.5 - 1,5 meter
- CLA712/3 - 3 meter

We reserve the right to change specifications without notice, this is part of our policy to continually improve our products.

SIG144
Signal Cable

This cable is a cable only used as a productioncomponent for PROCAB pre-made cables and is not sold seperately or in bulk. Consult the productsheet for detailed information.

We reserve the right to change specifications without notice, this is part of our policy to continually improve our products.