

## Quick Start Guide

### Classic Adaptor

for PCS-Boom Connector (185807)

### Cyclone Adaptor

for PCS-Boom Connector (185808)

Thank you for choosing this 'Adaptor' for the Rycote PCS-Boom Connector! This guide provides you with the basics to get you started.

This guide applies to both Adaptors, but only one Adaptor type is provided in the box - Classic or Cyclone.

Full details about this product are available on our website: [rycote.com/microphone-windshield-shock-mount/pcs-boom-range/](http://rycote.com/microphone-windshield-shock-mount/pcs-boom-range/)

## Overview

The Professional Connection System ('PCS') is the ingenious quick attach and release system from Rycote, and the PCS-Boom Connector (not included), has been designed for professional boom pole use.

The Classic Adaptor and Cyclone Adaptor for the PCS-Boom Connector offer the neatest, lightest and simplest way to integrate 'PCS' connectivity into your existing Rycote windshield kit (\*see 'Compatibility').

## Product view

### Classic Adaptor



### Cyclone Adaptor



## Compatibility

### Classic Adaptor

for PCS-Boom Connector (185807)

Rycote Modular and Pre-Modular Windshield Kits; Super-Shield Kits; 'Perfect For' Windshield Kits; Classic-Softie® Kits and other Rycote mounts fitted with a boom adaptor (replacing the existing boom adaptor or pistol grip handle)

### Cyclone Adaptor

for PCS-Boom Connector (185808)

Rycote Cyclone and Stereo Cyclone Windshield Kits (replacing the existing boom adaptor)

## Classic Adaptor Cyclone Adaptor for PCS-Boom Connector



Quick Start Guide  
Applies to both Adaptors

## Getting started

### Remove existing boom adaptor

- Unscrew the boom adaptor (or handle) from your windshield, and pull out your XLR connector from the existing XLR holder (by loosening the holder's screw)

Your windshield kit will now look like the following (examples shown for Rycote Modular and Cyclone Windshield Kits)



### Replace existing boom adaptor with your new Classic or Cyclone PCS Adaptor

- Unscrew the ratchet lever from the PCS Adaptor, and slide out the bolt

- Offer up the PCS Adaptor to the boss on your windshield (example below shows Classic PCS Adaptor & Modular Windshield Kit)



- **N.B.** both Classic and Cyclone PCS Adaptors are supplied with a black washer (thin, circular disc). Make sure that this washer is fitted in between the 'face' of the Adaptor and the boss of the windshield. This ensures a tight connection and prevents any unwanted slipping/movement
- The Classic Adaptor is also supplied with a smaller, white plastic washer, which should be fitted onto the bolt from the other side of the boss (as shown in following image)



- Once in place, screw the ratchet lever back on to the thread of the bolt and tighten (rotate clockwise)

### Attaching the XLR connector to the XLR holder on your new Classic or Cyclone PCS Adaptor

- Loosen the outer screw, which tightens/loosens the outer ring of the XLR holder, with a 'Philips head' screw driver. Push the XLR connector into the holder until the larger end of the XLR connector touches the holder
- Rotate the connector to your preferred position. **N.B.** Keep in mind that you have to be able to reach the XLR release button on the female connector when you attach a cable, or plug-on transmitter

- Lock the position by tightening the outer screw

### Rotating the XLR holder to your preferred position

- Loosen the inner screw, which tightens/loosens the inner ring of the XLR holder, with a 'Philips head' screw driver
- Pull the entire XLR holder down (in direction marked by arrow on XLR holder) and rotate the XLR holder to your preferred position
- Then push the XLR holder all the way back up again, making sure that the 'grid' slides into the 'teeth' completely.
- Secure in place by tightening the inner screw again, with a 'Philips head' screw driver.



 **Rycote**<sup>®</sup>

Trusted by Professionals

Rycote Microphone Windshields Ltd

Libby's Drive, Slad Road, Stroud, Glos, GL5 1RN, U.K.

Email: [tech\\_support@rycote.com](mailto:tech_support@rycote.com)

Web: [rycote.com](http://rycote.com)

Tel: +44 (0) 1453 759338

10/2018