

LDP-COBWASH 100WW 05176

DESCRIPTION

Powerful indoor / outdoor IP65 LED projector equipped with a WHITE COB led

FEATURES

- Powerful indoor / outdoor IP65 LED projector equipped with a WHITE COB led.
- **100 Watt model:** bigger enclosure, equipped with a 100W COB led for larger applications.
- WW (warm white): 3200K for a warm and cozy atmosphere
- Thanks to the very wide beam angle, this projector is the perfect solution for "close range" applications like wall washing but also great on concert stages, in theaters, discotheques, exhibition booths, ...
- Completely silent operation, thanks to natural convection cooling system.
- Backlit alphanumeric LCD-display and waterproof touch keys to select different options of the setup menu.
 - Standalone (master): set dimmer + strobe (if needed)
 - Master/slave mode: connect several projectors together, the first projector controls the others.
 - DMX-controlled, 1CH: dimmer
 - DMX-controlled, 2CH: dimmer, strobe
- IR-remote controller included: no difficult controllers needed!
- Selectable lamp behavior: halogen lamp (slow) or led (fast)
- Four dimmer curves: linear, square, inverse square, S-curve
- In case of DMX failure you can choose between blackout and freeze mode.
- Lock function to avoid unwanted altering of the settings.
- Special waterproof power in/outputs: easy daisy chaining of several units.
- Special waterproof DMX in/outputs with adapter cables to XLR for maximum compatibility
- Strong multifunctional bracket, designed for both fixed floor and truss mounting.
- Barn doors included and already installed



www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2017 by BEGLEC NV. All rights reserved.



SPECIFICATIONS

General : Application	Architectural
General : Dimensions (cm)	32.6 x 34.4 x 22.0 cm
General : Weight (kg)	8.2
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	120
General : Color	white
General : Display	LCD
General : IP rating	indoor, outdoor
Control : manual	No
Control : Master/Slave	Yes
Control : SMART-DMX	No
Control : Standalone	automatic
Control : Type included remote	IR-remote
Control : programmable	No
Control : upgradable software	No
Control : maximum DMX channels	2
Light : lamp socket	No
Light : lumen	4750
Light : lamp	COB
Light : min. color temperature (K)	3200
Light : max. color temperature (K)	3200
Light : CRI	85
Light : colors	Warm white
Light : mix colors	No
Light : focus	No
Light : zoom	No
Light : iris	No
Light : frost filter	No
Light : min. beam angle (°)	80
Light : max. beam angle (°)	80
Light : min. refresh rate (kHz)	3.6
Light : max. refresh rate (kHz)	3.6
Connections : input	3 pin XLR
Connections : output	3 pin XLR
Brand	BRITEQ
EANCode	5420025651769
Discontinued	No



YOUR DEALER



www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2017 by BEGLEC NV. All rights reserved.